



The Accord Product Line's MGC is the only Multipoint Control Unit (MCU) which functions both as a multimedia processor and a H.3xx gateway. It supports ITU-T standards for multipoint multimedia bridging devices and variable port bandwidth ranging from 56Kbps to 2Mbps.

## BROADBAND VISUAL COMMUNICATIONS ARCHITECTURE

The MGC-100 is a robust telecom architecture that maximizes system availability.

- Designed to incorporate new networks and new standards as they emerge, all in a **single platform**
- All ports, regardless of their networks, can use all advanced features therefore protecting investment
- On-line diagnostics to anticipate any potential problem
- Front panel LED lights for fast problem isolation
- All modules are:
  - Front-accessible
  - Hot-swappable
  - Self-configuring
- Full redundancy with up to three hot-swappable, load-sharing power supplies
- NEBS compliant chassis available
- High speed multimedia bus

## MULTI-NETWORK CONNECTIVITY

The MGC-100 provides IP, ISDN and ATM connectivity in a single platform.

- Connects directly with H.323 (IP) networks
- Supports H.320 (ISDN) and H.321 (ATM) networks
- Designed to incorporate new standards as they emerge such as 3GPP, all within a single platform
- All supported networks can access and utilize the MGC-100's advanced features
- NO external gateways necessary

## Advanced Features That Make A Difference!

The MGC-100 provides the most advanced features of any MCU.

Now you can produce your conference any way you want, making the remote meeting experience more like a face-to-face meeting.

### Continuous Presence

- Up to 21 different layouts
- Layouts changeable 'on-the-fly'
- Each window within each layout can be set as fixed or voice activated

### Multi-Way Transcoding

- Allows sites with different frame rates, connection speeds, audio algorithms, resolutions, and network protocols to transparently connect with one another
- Ensures that all sites connect at their optimal capabilities
- Ensures that conferences start on time by simplifying the connection process
- Ensures conference reliability

### Greet and Guide™ (ISDN and ATM)

- Customizable conference welcome screens and audio greeting messages
- Operator(s) can guide users through every part of the conference:
  - Greet users as they connect
  - Drag and drop participants between conferences
  - Create subconferences

### Powerful Management System

The MGC-100 provides the most flexible suite of system and conference management applications of any MCU. Three different management applications are offered to provide the power and flexibility required for both local and remote access and support.

- WebCommander™ empowers users to schedule and manage their own conferences using Netscape or Microsoft Web browsers
- MGC Manager™ provides comprehensive operator control - from conference scheduling and management to system configuration, diagnostics and maintenance
- Touch Tone Conference Manager (TTCM) empowers users to manage their own conferences using a standard touch-tone telephone

### Easy Maintenance

The MGC-100 reduces the need for on-site maintenance through advanced remote system monitoring tools.

- Remote diagnostics and problem resolution
- Remote software downloads
- Support for multiple MGC systems

### Reliability

The Accord Product Line's MGC-100 is the only carrier class solution for video and voice communications providing NEBS Level 3 compliance, making it the choice for mission critical applications.

*Rich Media Communications is a real-time virtual communications experience... anytime, anywhere. The Accord Product Line provides the tools that make virtual communications a reality, enhancing the way people communicate and interact. With the Accord Product Line the user is ensured of a networking solution which makes rich media applications such as business conferencing, telemedicine, distance learning, visual enabled e-commerce, visual call centers and visual chat rooms a reality.*



## System Capacity



	ISDN	ATM	IP
Max No. Sites	96	80	144*
Max No. Simultaneous Conferences	32	28	48
Max No. CP conferences	16	13	16
<b>Videoconferencing</b>	<ul style="list-style-type: none"> <li>• H.320, H.323, H.321, T.120</li> </ul>		
<b>Telephony</b>	<ul style="list-style-type: none"> <li>• PSTN, VoIP</li> </ul>		
<b>Multi-way</b>	<ul style="list-style-type: none"> <li>• H.231, H.243 Cascading and Chair Control</li> <li>• H.281 FECC (Far End Camera Control)</li> </ul>		
<b>Video</b>	<ul style="list-style-type: none"> <li>• H.261, H.263, H.263+</li> </ul>		
<b>Audio</b>	<ul style="list-style-type: none"> <li>• G.711, G.722.1, G.723, G.728, Siren 7 (16, 24, 32Kbps)</li> </ul>		
<b>Data</b>	<ul style="list-style-type: none"> <li>• H.243 LSD, T.122/T.125 (MCS), T.123, T.124 (GCC)</li> </ul>		
<b>Communications</b>	<ul style="list-style-type: none"> <li>• H.221, H.242</li> </ul>		
<b>Channel aggregation</b>	<ul style="list-style-type: none"> <li>• H.221, BONDING Mode 1, H0</li> </ul>		

### EXTERNAL COMMUNICATIONS

<b>Data rates</b>	<ul style="list-style-type: none"> <li>• 56Kbps - 2Mbps</li> </ul>
<b>Clock synchronization</b>	<ul style="list-style-type: none"> <li>• Synchronizes to external network</li> </ul>

### NETWORK INTERFACES

<b>25 Mbps ATM (FVC)</b>	<ul style="list-style-type: none"> <li>• PRI-T1 (ISDN signaling)</li> </ul>	<ul style="list-style-type: none"> <li>• V.35/RS-449/EIA-530</li> </ul>
<b>55 Mbps ATM (FVC)</b>	<ul style="list-style-type: none"> <li>• E1/T1 Leased Line</li> </ul>	<ul style="list-style-type: none"> <li>• RS-366 dialing</li> </ul>
<b>100/10 Mbps Ethernet</b>	<ul style="list-style-type: none"> <li>• PRI-E1 (ISDN signaling)</li> </ul>	<ul style="list-style-type: none"> <li>• KG Support</li> </ul>

### ENVIRONMENT

<b>Operating temperature</b>	<ul style="list-style-type: none"> <li>• 10 to 40°C (50 to 104°F)</li> <li>• 3400 BTU per hour</li> </ul>
<b>Storage temperature</b>	<ul style="list-style-type: none"> <li>• -25 to 70°C (-20 to 158°F)</li> </ul>
<b>Relative humidity</b>	<ul style="list-style-type: none"> <li>• 15 to 90% non condensing</li> </ul>
<b>Operating altitude</b>	<ul style="list-style-type: none"> <li>• Up to about 3,000m (10,000ft)</li> </ul>
<b>Storage altitude</b>	<ul style="list-style-type: none"> <li>• Up to about 12,000m (40,000ft)</li> </ul>
<b>Operating ESD</b>	<ul style="list-style-type: none"> <li>• +8 kV</li> </ul>
<b>Storage ESD</b>	<ul style="list-style-type: none"> <li>• +15 kV</li> </ul>

### PHYSICAL

<b>NEBS</b>	<ul style="list-style-type: none"> <li>• Level 3 Compliant</li> </ul>
<b>Height</b>	<ul style="list-style-type: none"> <li>• 40.8 cm (16 inches)</li> </ul>
<b>Width</b>	<ul style="list-style-type: none"> <li>• 58.4 cm (23 inches)</li> </ul>
<b>Depth</b>	<ul style="list-style-type: none"> <li>• 50.2 cm (19 inches)</li> </ul>
<b>Weight</b>	<ul style="list-style-type: none"> <li>• Net 43kg (94lbs), including packaging 64kg (140lbs)</li> </ul>
<b>Power Supply x 3 load sharing</b>	<ul style="list-style-type: none"> <li>• 110-240 VAC</li> <li>• 50/60 Hz</li> <li>• -48 DC</li> </ul>

\* Available second half 2001

#### US OFFICE

Atlanta, Georgia, USA  
**Phone:** +1 770 641 4400  
**Fax:** +1 770 641 4499

#### EUROPEAN OFFICE

Hare Hatch, Berkshire, UK  
**Phone:** +44 1189 704400  
**Fax:** +44 1189 704499

#### ISRAEL OFFICE

Petach-Tikva, Israel  
**Phone:** +972 3 925 1444  
**Fax:** +972 3 921 1571

#### ASIA OFFICE

Beijing, China  
**Phone:** +86 10 65908321  
**Fax:** +86 10 65908368

